

Name \_\_\_\_\_

Company \_\_\_\_\_ Customer number \_\_\_\_\_

Address \_\_\_\_\_ Postal code \_\_\_\_\_ City \_\_\_\_\_

Phone \_\_\_\_\_ E-mail \_\_\_\_\_

Order  Request

## SKYFORCE

Type:  SKYFORCE Top Mount  SKYFORCE Side Mount  SKYFORCE SLIM Top/Side Mount

Please indicate the desired finish and quantity:

Glass height	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm	<input type="checkbox"/> or a special height up to max. 1200 mm _____ mm
up to 1200 mm/10.76 mm	inadmissible	inadmissible					
up to 1400 mm/12.76 mm							
up to 1700 mm/17.52 mm							
up to 3000 mm/21.52 mm							

Finish

Mill finish (.10)  EV1 (.11)  RAL: \_\_\_\_\_ shiny (.13) / structured matt (.16) / matt (.18)  RAL 7016 (.13/.18)

## Fixing


Fixing on plastic  
Self-tapping screw



Length B in mm: \_\_\_\_\_

Number of Skyforce sets: \_\_\_\_\_

12 items per sales unit/required for one Skyforce set



Fixing on concrete  
**not suitable for SKYFORCE SLIM**

Top  Side  Slim



Fixing on wood

Top  Side  Slim




Fixing on aluminium  
Self-tapping screw



Length: 45 mm

Number of Skyforce sets: \_\_\_\_\_

12 items per sales unit/required for one Skyforce set



Spacer sleeve for hollow chambers  
(shutter guide rails/wood/aluminium)

10.5 mm  20.5 mm  
 16 mm  60 mm (can be trimmed to size)


Fixing on plastic & aluminium, stainless steel screw  
**not suitable for SKYFORCE SLIM**



Length B in mm: \_\_\_\_\_

Number of Skyforce sets: \_\_\_\_\_

12 items per sales unit/required for one Skyforce set



Drill for stainless steel screw

Ø5 mm (for 1.5 mm wall thickness)  
 Ø5.3 mm (for 2.0 - 4.0 mm wall thickness)

## Edge protection

Glass thickness: \_\_\_\_\_ Length in mm: \_\_\_\_\_

Please note the insert dimensions: Skyforce Top: 15 mm on each side  
Skyforce Side: 12.5 mm on each side  
Skyforce Slim: 13.5 mm on each side

Surface

mill finish (.10)  EV1 (.11)  RAL: \_\_\_\_\_ shiny (.13) / structured matt (.16) / matt (.18)  RAL 7016 (.13/.18)  V4A