

Name _____

Company _____ Customer number _____

Address _____ Postal code _____ City _____

Phone _____ E-mail _____

Order Request

SKYFORCE

Type: SKYFORCE Top Mount SKYFORCE Side Mount SKYFORCE SLIM Top/Side Mount

Please indicate the desired finish and quantity:

Glass height \ Width	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm	<input type="checkbox"/> or a special height up to max. 1200 mm _____ mm
up to 1200 mm/10.76 mm	inadmissible	inadmissible					
up to 1400 mm/12.76 mm							
up to 1700 mm/17.52 mm							
up to 3000 mm/21.52 mm							

Finish

Mill finish (.10) EV1 (.11) RAL: _____ shiny (.13) / structured matt (.16) / matt (.18) RAL 7016 (.13/.18)

Fixing


Fixing on plastic
Self-tapping screw



Length B in mm: _____

Number of Skyforce sets: _____

12 items per sales unit/required for one Skyforce set



Fixing on concrete
not suitable for SKYFORCE SLIM

Top Side Slim



Fixing on wood

Top Side Slim




Fixing on aluminium
Self-tapping screw



Length: 45 mm

Number of Skyforce sets: _____

12 items per sales unit/required for one Skyforce set



Spacer sleeve for hollow chambers
(shutter guide rails/wood/aluminium)

10.5 mm 20.5 mm
 16 mm 60 mm (can be trimmed to size)


Fixing on plastic & aluminium, stainless steel screw
not suitable for SKYFORCE SLIM



Length B in mm: _____

Number of Skyforce sets: _____

12 items per sales unit/required for one Skyforce set



Drill for stainless steel screw

Ø5 mm (for 1.5 mm wall thickness)
 Ø5.3 mm (for 2.0 - 4.0 mm wall thickness)

Edge protection

Glass thickness: _____ Length in mm: _____

Please note the insert dimensions: Skyforce Top: 15 mm on each side
Skyforce Side: 12.5 mm on each side
Skyforce Slim: 13.5 mm on each side

Surface

mill finish (.10) EV1 (.11) RAL: _____ shiny (.13) / structured matt (.16) / matt (.18) RAL 7016 (.13/.18) V4A