

# ONLEVEL | FLEXFIT VERSTELBAARHEID

GLASDIKTE 1.0 kN	WINKEL	GLASHOOGTE 1000 mm	GLASHOOGTE 1100 mm	GLASHOOGTE 1200 mm
		VERSTELBAARHEID	VERSTELBAARHEID	VERSTELBAARHEID
12 mm	1,6°	28 mm	30 mm	34 mm
12,76 mm (6/6/2)	1,6°	28 mm	30 mm	34 mm
13,52 mm (6/6/4)	1,6°	28 mm	30 mm	34 mm
15 mm	1,6°	28 mm	30 mm	34 mm
16,76 mm (8/8/2)	1,0°	28 mm	30 mm	34 mm
17,52 mm (8/8/4)	1,6°	28 mm	30 mm	34 mm
19 mm	1,0°	18 mm	20 mm	22 mm
20,76 mm (10/10/2)	1,0°	18 mm	20 mm	22 mm
21,52 mm (10/10/4)	1,0°	18 mm	20 mm	22 mm

GLASDIKTE 3.0 kN	WINKEL	GLASHOOGTE 1000 mm	GLASHOOGTE 1100 mm	GLASHOOGTE 1200 mm
		VERSTELBAARHEID	VERSTELBAARHEID	VERSTELBAARHEID
21,52 mm (10/10/4)	1,0°	28 mm	30 mm	34 mm
25,52 mm (12/12/4)	1,6°	28 mm	30 mm	34 mm
31,52 mm (15/15/4)	1,0°	18 mm	20 mm	22 mm

